

### A class Solid State High VSWR operation

Application : Radiated and Conducted EMC

Designed and manufactured in Europe, the AP32DR225 power amplifier operates in a symmetric mode with high linearity capability. Solid state power modules are combined with high performance proprietary devices.

Its very wide bandwidth allows a full Bulk Current Injection test with no band switching.

PRANA back ground into high power and broadband EMC products in last 20 years brings products to high reliability.

A high linear power is available at low frequencies and allows a high field output level with typical broadband antennas. PRANA EMC amplifiers are designed to withstand excessive VSWR of typical EMC field generation or current injection load mismatch.

The AP32DR225 amplifier is compatible with any automatic test environment thanks to additional measurement and communication features.

The up to date and modern concept of the AP32DR225 amplifier warrants the user of a permanent internal signal levels monitoring and allows local or remote full diagnostic capability.



## Output characteristics

Nominal power	250 W
Single Instantaneous range	10kHz – 400MHz
Power at 3 dB compression	280 W min.
Power at 1 dB compression	230 W min.
Gain	54 dB typ.
Linear power gain flatness	± 0.75dB typ. / ± 1.5 dB max.
Nominal output load	50 Ohms
Reflected Power on load mismatch	300 W reverse power without power protection
Harmonic distortion at 1dB comp. or nominal power	H2 <-25 dBc / -30 dBc typ. H3 <-20 dBc / -25 dBc typ.
Spurious	< -50dBc
Noise figure for F>50MHz	< 20dB typ. / 25dB max.

## Input characteristics

Input level for nominal output power	0 dBm typ.
Input impedance	50 Ohms
Input VSWR	2:1 max.
Maximum input level	+10dBm

## External interface

RF Input connector (1)	Type N fem.
RF output connector (1)	Type N fem.
Incident and reflected RF power sample connector (2)	Type N fem. (option 001)
Safety interlock	Yes
Communication IEEE 488 GPIB	Yes
Digital display	Yes
LED control indicator	Fault, Controller Ok
Forward and direct power display	Yes (Option 003)
Manual controls	Power On/Off – menu key functions

## Environment and Protections

Ambient temperature range in operation	0°C / +35°C
Storage ambient temperature range	-20°C / +70°C
Cooling	Air, 120 l/sec max.
Protections	Infinite VSWR, Temperature, Power Supply, Bias Voltage
EMC	CE Certified

## Electrical characteristics

Supply voltage	200-250 VAC, 47-63Hz, single phase
Nominal current	< 10.8 A at 230V AC
Power in	< 2400 VA

## Mechanical outline

Packaging	19" Rack
High (standard)	267 mm (6U)
Width	450 mm
Depth	630 mm
Weight	62 kg

- (1) Front panel Standard,  
(2) Rear panel only.

### Power graph

