

**A class Solid State  
High VSWR operation**

**Application : Radiated EMC**

Designed and manufactured in France, the AP32 NT215 power amplifier operates in a symmetric mode with high linearity capability. Solid state power modules are combined with high performance proprietary devices.

PRANA back ground into high power and broadband EMC products in last 20 years brings products to high reliability.

A high linear power is available and allows a high field output level with typical broadband antennas. PRANA EMC amplifiers are designed to withstand excessive VSWR of typical EMC field generation environment.

The AP32 NT215 amplifier is compatible with any automatic test environment thanks to additional measurement and communication features.

The up to date and modern concept of the AP32 NT215 amplifier warrants the user of a permanent internal signal levels monitoring and allows local or remote full diagnostic capability.



### Output characteristics

Nominal power	150 W
Single Instantaneous range	200 – 1000 MHz
Power at 3 dB compression (1)	150 W min. up to 600 MHz / 130 W min. up to 1 GHz
Power at 1 dB compression (1)	130 W min. up to 600 MHz / 110 W min. up to 1 GHz
Gain	51 dB typ.
Linear power gain flatness	± 2 dB typ. / ± 3 dB max.
Nominal output load	50 Ohms
Reflected power on load mismatch	150 W reverse power without power protection
Harmonic distortion at 1dB compression or nominal power	H2 < -25 dBc / -30 dBc typ. H3 < -20 dBc / -25 dBc typ.
Spurious	< -60 dBc
Noise figure	< 20 dB typ. / 25 dB max.


### Input characteristics

Input level for nominal output power	0 dBm typ.
Input impedance	50 Ohms
Input VSWR	2:1 max.
Maximum input level	+10 dBm

### External interface

RF input connector (2)	Type N fem.
RF output connector (2)	Type N fem.
Incident and reflected RF power sample connector (3)	Type N fem. (Option 001)
Safety interlock	Yes
Communication IEEE 488 GPIB	Yes
Digital display	Yes
LED control indicator	Fault, Controller Ok
Forward and direct power display	Yes (Option 003)
Manual controls	Power On/Off – menu key functions

### Environment and Protections

Ambient temperature range in operation	0°C / +35°C
Storage ambient temperature range	-20°C / +70°C
Cooling	Air, 60 l/sec
Protections	Infinite VSWR, Temperature, Power Supply, Bias Voltage
EMC	 certified

### Electrical characteristics

Supply voltage	90 -250 VAC, 47-63Hz, single phase
Nominal current	12.7 A at 110 V - 6 A at 230 V
Power in	< 1400 VA

### Mechanical outline

Packaging	19" Rack
High (standard)	178 mm (4U)
Width	450 mm
Depth	630 mm
Weight	34 kg

(1) Without internal coupler (Option 001).

(2) Front panel standard.

(3) Rear panel standard.

### Power graph

