

A class Solid State  
High VSWR operation

Application : Radiated EMC



The AP32 TU125 power amplifier operates in a symmetric mode with high linearity capability. Solid state power modules are combined with high performance proprietary devices.

A high linear power is available and allows a high field output level with typical broadband antennas.


PRANA EMC amplifiers are designed to withstand excessive VSWR of typical EMC field generation environment.

The AP32 TU125 amplifier is compatible with any automatic test environment thanks to additional measurement and communication features.

The up to date and modern concept of the AP32 TU125 amplifier warrants the user of a permanent internal signal levels monitoring and allows local or remote full diagnostic capability.

PRÂNA

AP32 TU125 POWER AMPLIFIER - 25W / 1GHz - 2GHz - Typical Power



### Output characteristics

Nominal power	25 W
Single Instantaneous range	1000 – 2000 MHz
Power at 3 dB compression max. (1)	27W min.
Power at 1 dB compression max. (1)	22 W min.
Gain	44 dB typ., 41 dB min.
Linear power gain flatness	± 3 dB typ., ± 3.5 dB max.
Nominal output load	50 Ohms
Reflected power on load mismatch	100 % reverse power without power protection
Harmonic distortion at 1dB compression or nominal power	H2 < -20 dBc H3 < -20 dBc
Spurious	< -60 dBc
Noise figure	≤ 15 dB typ.

### Input characteristics

Input level for nominal output power	0 dBm typ.
Input impedance	50 Ohms
Input VSWR	2:1 max.
Maximum input level	+10 dBm

### External interface

RF input connector (2)	Coaxial N fem.
RF output connector (2)	Coaxial N fem.
Incident power sampling connector (3)	Coaxial N fem. (Option 001)
Reflected RF power sampling connector (3)	Coaxial N fem. (Option 001)
Communication IEEE 488 GPIB	Option 002
Digital display	Yes
LED control indicator	Fault, Controller Ok
Forward and direct power display	Option 003
Manual controls	Power On/Off – menu key functions

### Environment and Protections

Ambient temperature range in operation	0°C / +35°C
Storage ambient temperature range	-20°C / +70°C
Cooling	Air, 60 l/sec
Protections	Infinite VSWR, Temperature, Power Supply, Bias Voltage
EMC	CE certified

### Electrical characteristics

Supply voltage (4)	90-250 VAC, 47-63 Hz
Nominal current	2.1 A at 100 V – 0.9 A at 230 V
Power in	< 230 VA

### Mechanical outline

Packaging	19" RACK
High (standard)	178 mm (4U)
Width	450 mm
Depth	630 mm
Weight	30 kg

- (1) Without Option 001 (Internal coupler).
- (2) Front panel standard / Rear panel on request.
- (3) Rear panel standard / Front panel on request.
- (4) Other voltage or frequency on request.